

10-30-00

10/27/00
JC926 U.S. PRO

PATENT APPLICATION
Attorney's Do. No. 2705-133


IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

09/698885 PRO
10/27/00

CERTIFICATE OF EXPRESS MAILING
MAILING LABEL NO. EL532245309US
DATE OF DEPOSIT: OCTOBER 27, 2000

I HEREBY CERTIFY THAT THIS PAPER AND ENCLOSURES AND/OR FEE ARE BEING DEPOSITED WITH THE UNITED STATES POSTAL SERVICE "EXPRESS MAIL POST OFFICE TO ADDRESSEE" SERVICE UNDER 37 CFR 1.10 ON THE DATE INDICATED ABOVE AND IS ADDRESSED TO: BOX PATENT APPLICATION, ASSISTANT COMMISSIONER FOR PATENTS, WASHINGTON D.C. 20231.

EHREN RHEA
(SENDER'S PRINTED NAME)


(SIGNATURE)

Box Patent Application
Assistant Commissioner for Patents
Washington, D.C. 20231

Enclosed for filing is a patent application under 37 CFR 1.53(b) of:

Inventor: Thomas J. Hock

For: **DEVICES, SOFTWARE AND METHODS FOR DETERMINING A QUALITY OF SERVICE FOR A VoIP CONNECTION**

Enclosures:

- Specification (pages 1-8); claims (pages 9-13); abstract (page 14)
- 2 sheet(s) of FORMAL drawings
- Declaration or Combined Declaration and Power of Attorney
 - Newly executed (original or copy)
 - Copy from a prior application (37 CFR 1.63(d))
 - Incorporation by Reference--The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
 - Deletion of Inventors (signed statement attached deleting inventor(s) named in the prior application (37 CFR 1.63(d)(2) and 1.33(b))
 - Power of Attorney

- Assignment with cover sheet
 Certified copy of priority document:
 Information Disclosure Statement with Form PTO 1449
 Copies of references listed on attached Form PTO-1449
 Preliminary Amendment
 Change of Address
 Return Postcard


<u>CLAIMS AS FILED</u>				
For	Number Filed	Number Extra	Rate	Basic Fee
Total Claims	24-20	4	x \$ 18 =	\$ 72
Independent Claims	4-3	1	x \$ 80 =	\$ 80
TOTAL FILING FEE				\$862

- A check in the amount of \$902 to cover filing fee and assignment recordation fee (\$40) is enclosed.
 Any deficiency or overpayment should be charged or credited to deposit account number 13-1703. A duplicate copy of this sheet is enclosed.

Customer No. 20575

Respectfully submitted,

MARGER JOHNSON & McCOLLOM, P.C.



Gregory T. Kavounas, Reg. No. 37,862

MARGER JOHNSON & McCOLLOM, P.C.
 1030 SW Morrison Street
 Portland, OR 97205
 (503) 222-3613

DOCKET NO. 2705-133

UNITED STATES OF AMERICA

APPLICATION FOR PATENT

FOR INVENTION OF

**DEVICES, SOFTWARE AND METHODS FOR DETERMINING
A QUALITY OF SERVICE FOR A VoIP CONNECTION**

Inventor: Thomas Hock

Application prepared by: Marger Johnson & McCollom
1030 S.W. Morrison Street
Portland, Oregon 97205 USA
tel: (503) 222-3613
fax: (503) 274-4622
www.techlaw.com

**DEVICES, SOFTWARE AND METHODS FOR DETERMINING
A QUALITY OF SERVICE FOR A VoIP CONNECTION**

BACKGROUND OF THE INVENTION

5 1. Field of the invention.

The present invention is related to the field of network telephony, and more specifically to devices, software and methods for determining a quality of voice connection between network devices.

10 2. Description of the related art.

The internet is used for telephony, in addition to sending data. Accordingly, voice is encoded into digital data, the data is arranged in packets, and the packets are transmitted to the recipient over a network. This process has to happen in real time, which means that the familiar Transmission Control Protocol/Internet Protocol (TCP/IP) can not be used. Instead, other protocols are used, which permit real time use, such as the Uniform Datagram Protocol (UDP).

A disadvantage of protocols that permit real time use is that they are unreliable, in that they permit packets to be lost, without retrieving them. When that happens, the voice segments they were carrying are not reconstructed. If these are many, then the recipient hears annoying gaps in the reconstructed speech.

BRIEF SUMMARY OF THE INVENTION

The present invention overcomes these problems and limitations of the prior art.

Generally, the present invention provides devices, software and methods for 25 determining a quality of service for a Voice over Internet Protocol (VoIP) connection. Corrective measures can be taken if the quality of service is determined to be below a threshold.

The devices, software and methods of the invention measure a round trip time of 30 packets between the devices that are exchanging voice data, and also at least one performance parameter. A quality of service is then determined from the round trip time and the performance parameter.

The invention will become more readily apparent from the following Detailed Description, which proceeds with reference to the drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a block diagram of a transmitting device made according to an embodiment of the invention.

Fig. 2 is a block diagram of a receiving device made according to another embodiment of the invention.

10 Fig. 3 is a flowchart illustrating a method according to an embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

As has been mentioned, the present invention provides devices, software and methods for determining a quality of service for a Voice over Internet Protocol (VoIP) connection. The invention is now described in more detail.

Referring to Fig. 1, a transmitting device 100 made according to an embodiment of the invention is described. Device 100 is for transmitting voice packets through a network 20. Device 100 preferably transmits the voice packets to a network switch 40, such as Gateway-A 40, of the network 20.

20 One or more of the components of device 100 can be implemented in combination with each other, consistently with components of this description. For example, device 100 can be implemented as part of a larger Digital Signal Processing (DSP) architecture.

In the embodiment of Fig. 1, device 100 includes an encoder 110 for encoding a frame of voice data into a voice packet. Encoder 110 includes a processor 112, which is 25 also referred to as Central Processing Unit (CPU) 112, and a memory 114. The processor 112 is adapted to perform the method of the invention. Preferably it is so adapted by running a program 116 made according to the invention, which resides on memory 114.

In addition, device 100 optionally includes a transmit buffer 130 adapted to receive inputs from the encoder 110, for storing the encoded frames prior to transmitting.

Device 100 includes a network interface (not shown separately) for interfacing with network 20. The network interface can be implemented as a stand-alone feature, or in conjunction with another component, such as transmit buffer 130.

Referring to Fig. 2, a receiving device 200 according to the invention is described.

- 5 One or more of the components of device 200 can be implemented in combination with each other, consistently with components of this description. For example, device 200 can be implemented as part of a larger Digital Signal Processing (DSP) architecture.

In the embodiment of Fig. 2, device 200 includes a jitter buffer 210. This stores a number of frames as they are received from the network 20. The jitter buffer thus
10 prevents an anomaly that could be experienced, if frames were played out exactly when they are received. Due to the nature of transmission through the network 20, they can be received in bunches, with gaps between the bunches. Jitter buffer 210 permits playing them out at a regular pace, notwithstanding when exactly they are received.

- 15 Device 200 also includes a decoder 270. Decoder 270 includes a processor 272, which is also referred to as Central Processing Unit (CPU) 272, and a memory 274. The processor 272 is adapted to perform the method of the invention. Preferably it is so adapted by running a program 276 made according to the invention, which resides on memory 274.

- 20 Device 200 can also include other components, such as a Digital to Analog Converter (DAC) 280. This converts the decoded voice data into an analog signal, which can be input in a speaker 290.

- 25 Device 200 includes a network interface (not shown separately) for interfacing with network 20. The network interface can be implemented as a stand-alone feature, or in conjunction with another component, such as jitter buffer 210. Device 200 is deemed to interface with a network switch 60, such as Gateway-B 60, of network 20.

As an example, a device that may incorporate aspects of the present invention would be an Internet Protocol (IP) telephone. Its transmitting side could include device 100 of Fig. 1, while its receiving side could include device 200 of Fig. 2.

- 30 A device of the invention need not be limited to two-way voice communication. Devices, software and methods for one way transmitting, such as broadcasting, are also included.

It is readily apparent that the present invention can be implemented by one or more devices that include logic circuitry. It can also be implemented by a device that includes a dedicated processor system, that can include a microcontroller or a microprocessor.

5 The invention additionally provides methods, which are described below.

Moreover, the invention provides apparatus that performs, or assists in performing the methods of the invention. This apparatus may be specially constructed for the required purposes, or it may comprise a general-purpose computer selectively activated or reconfigured by a computer program stored in the computer. The methods and

10 algorithms presented herein are not necessarily inherently related to any particular computer or other apparatus. In particular, various general-purpose machines may be used with programs in accordance with the teachings herein, or it may prove more convenient to construct more specialized apparatus to perform the required method steps.

The required structure for a variety of these machines will appear from this description.

15 Useful machines or articles for performing the operations of the present invention include general-purpose digital computers or other similar devices. In all cases, there should be borne in mind the distinction between the method of operating a computer and the method of computation itself. The present invention relates also to method steps for operating a computer and for processing electrical or other physical signals to generate 20 other desired physical signals.

The invention additionally provides a program, and a method of operation of the program. The program is most advantageously implemented as a program for a computing machine, such as a general purpose computer, a special purpose computer, a microprocessor, etc.

25 The invention also provides a storage medium that has the program of the invention stored thereon. The storage medium is a computer-readable medium, such as a memory, and is read by the computing machine mentioned above.

A program is generally defined as a sequence of steps leading to a desired result. These steps, also known as instructions, are those requiring physical manipulations of 30 physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared,

and otherwise manipulated or processed. When stored, they can be stored in any computer-readable medium. It is convenient at times, principally for reasons of common usage, to refer to these signals as bits, data bits, samples, values, elements, symbols, characters, images, terms, numbers, or the like. It should be borne in mind, however, that
5 all of these and similar terms are associated with the appropriate physical quantities, and that these terms are merely convenient labels applied to these physical quantities.

This detailed description is presented largely in terms of flowcharts, display images, algorithms, and symbolic representations of operations of data bits within a computer readable medium, such as a memory. Such descriptions and representations are
10 the type of convenient labels used by those skilled in programming and/or the data processing arts to effectively convey the substance of their work to others skilled in the art. A person skilled in the art of programming can use this description to readily generate specific instructions for implementing a program according to the present invention. For the sake of economy, however, flowcharts used to describe methods of
15 the invention are not repeated in this document for describing software according to the invention.

Often, for the sake of convenience only, it is preferred to implement and describe a program as various interconnected distinct software modules or features, collectively also known as software. This is not necessary, however, and there may be cases where
20 modules are equivalently aggregated into a single program with unclear boundaries. In any event, the software modules or features of the present invention can be implemented by themselves, or in combination with others. Even though it is said that the program can be stored in a computer-readable medium, it should be clear to a person skilled in the art that it need not be a single memory, or even a single machine. Various portions,
25 modules or features of it can reside in separate memories, or even separate machines. The separate machines may be connected directly, or through a network, such as a local access network (LAN), or a global network, such as the Internet.

In the present case, methods of the invention are implemented by machine operations. In other words, embodiments of the program of the invention are made such
30 that they perform methods of the invention that are described in this document. These can be optionally performed in conjunction with one or more human operators

performing some, but not all of them. As per the above, the users need not be collocated with each other, but each only with a machine that houses a portion of the program.

Alternately, some of these machines can operate automatically, without users and/or independently from each other.

- 5 Referring now to Fig. 3, a flowchart 300 is used for illustrating a method of the invention.

According to a box 310, a Voice over Internet Protocol (VoIP) connection is established between a first device and a second device. For purposes of interpreting this document, the first device can be either device 100 or Gateway-A 40, and the second 10 device can be either device 200 or Gateway-B 60. In any one of these cases, the connection can be established through the network 20, and is for exchanging data packets that represent voice.

According to a next box 320, a round trip time RTT is determined for data packets being exchanged through the connection. This can be a single time, and measured by 15 sending and receiving back a scout packet.

According to a next box 330, a network connection impairment factor Idd is determined from the round trip time RTT. This box is not necessary for performing the invention, but a preferred embodiment of quantifying the round trip time RTT, for ultimately determining the quality of service of the connection. Since it is associated 20 with a delay, the network connection impairment factor Idd may be determined by dividing the RTT by 2. Other factors can be added in, such as known delay times. Such delay times can be a receive delay, and a fixed coder-decoder (“codec”) delay.

According to a next box 340, transmission of the data packets along the connection starts. More particularly, at least some data packets are transmitted.

25 According to a next box 350, at least one performance parameter is determined from transmitting the data packets. A distinct advantage of the invention is that the performance parameter is determined at a digital signal processing (DSP) stage. More particularly, the performance parameter can be determined from a voice sample loss, or from a voice sample delay at the DSP stage, or both.

For any one of these embodiments, the size of a jitter buffer may make a difference. Larger packet payloads may delay a packet, and fill the jitter buffer faster. In addition, a packet is deemed lost if it arrives too late for being played out.

According to a next box 360, a performance impairment factor I_e is determined from the performance parameter. This box is not necessary for performing the invention, but a preferred embodiment of quantifying the performance parameter, for ultimately determining the quality of service of the connection.

In one embodiment, packet loss can be quantified by adding together irregular gaps, that is those filled with silence, interpolation, prediction and redundancy. Then I_e can be computed as a function of the quantified loss.

Then according to the invention, a quality of service of the connection is determined from the round trip time and the performance parameter. In the preferred embodiment, this happens as follows:

According to a next box 370, a total impairment factor I_{tot} is determined from the performance impairment factor I_e and the network connection impairment factor I_{dd} . Then according to a next box 380, the quality of service is determined from the total impairment factor I_{tot} .

There are a number of ways for determining the total impairment factor I_{tot} . In the preferred embodiment, the network connection impairment factor I_{dd} is added together with the performance impairment factor I_e . Other factors can also be added or subtracted for the total impairment factor I_{tot} .

According to a next box 390, it is inquired whether the call over the connection has ended. If yes, then according to a next box 395, execution stops.

If the call has not ended, execution returns to box 340. Additional data packets are transmitted, and then an updated performance parameter is determined for the additional data packets. Accordingly, updated quality of service of the connection can be computed from the updated performance parameter.

A person skilled in the art will be able to practice the present invention in view of the description present in this document, which is to be taken as a whole. Numerous details have been set forth in order to provide a more thorough understanding of the

invention. In other instances, well-known features have not been described in detail in order not to obscure unnecessarily the invention.

While the invention has been disclosed in its preferred form, the specific embodiments thereof as disclosed and illustrated herein are not to be considered in a limiting sense. Indeed, it should be readily apparent to those skilled in the art in view of the present description that the invention can be modified in numerous ways. The inventor regards the subject matter of the invention to include all combinations and subcombinations of the various elements, features, functions and/or properties disclosed herein.

The following claims define certain combinations and subcombinations, which are regarded as novel and non-obvious. Additional claims for other combinations and subcombinations of features, functions, elements and/or properties may be presented in this or a related document.

15

CLAIMS

The invention claimed is:

- 5 1. A device comprising:
 - a network interface for coupling to a network; and
 - a processor coupled with the network interface, wherein the processor is adapted to establish a connection through the network for exchanging data packets that represent voice between the device and a corresponding device;
 - determine a round trip time for data packets being exchanged through the connection;
 - determine at least one performance parameter from transmitting a plurality of data packets along the connection; and
- 10 15 determine a quality of service of the connection from the round trip time and the performance parameter.
2. The device of claim 1, wherein the performance parameter is determined from a voice sample delay at a digital signal processing stage.
- 20 3. The device of claim 1, wherein the performance parameter is determined from a voice sample loss at a digital signal processing stage.
- 25 4. The device of claim 1, wherein the processor is further adapted to: determine a network connection impairment factor from the round trip time; and determine a performance impairment factor from the performance parameter, wherein the quality of service is determined from the network connection impairment factor and the performance impairment factor.
- 30

5. The device of claim 1, wherein
the quality of service is determined by adding together the network connection
impairment factor and the performance impairment factor.
- 5 6. The device of claim 1, wherein the processor is further adapted to:
determine an updated performance parameter from transmitting a plurality of
additional data packets; and
determine an updated quality of service of the connection from the updated
performance parameter.
- 10
7. An article comprising: a storage medium, said storage medium having stored
thereon instructions, that, when executed by a first device, result in:
establishing a connection through a network for exchanging data packets that
represent voice between the first device and a second device;
- 15 determining a round trip time for data packets being exchanged through the
connection;
determining at least one performance parameter from transmitting a plurality of
data packets along the connection; and
determining a quality of service of the connection from the round trip time and the
performance parameter.
- 20
8. The article of claim 7, wherein
the performance parameter is determined from a voice sample delay at a digital
signal processing stage.
- 25
9. The article of claim 7, wherein
the performance parameter is determined from a sample loss at a digital signal
processing stage.
- 30 10. The article of claim 7, wherein the instructions further result in:

determining a network connection impairment factor from the round trip time;
and

determining a performance impairment factor from the performance parameter,

wherein the quality of service is determined from the network connection

5 impairment factor and the performance impairment factor.

11. The article of claim 7, wherein

the quality of service is determined by adding together the network connection
impairment factor and the performance impairment factor.

10

12. The article of claim 7, wherein the instructions further result in:

determining an updated performance parameter from transmitting a plurality of
additional data packets; and

determining an updated quality of service of the connection from the updated

15 performance parameter.

13. A device comprising:

means for coupling to a network;

means for establishing a connection through the network for exchanging data

20 packets that represent voice between the device and a corresponding device;

means for determining a round trip time for data packets being exchanged through
the connection;

means for determining at least one performance parameter from transmitting a
plurality of data packets along the connection; and

25 means for determining a quality of service of the connection from the round trip
time and the performance parameter.

14. The device of claim 13, wherein

the performance parameter is determined from a voice sample delay at a digital

30 signal processing stage.

15. The device of claim 13, wherein
the performance parameter is determined from a voice sample loss at a digital
signal processing stage.
- 5 16. The device of claim 13, further comprising:
means for determining a network connection impairment factor from the round
trip time; and
means for determining a performance impairment factor from the performance
parameter,
10 wherein the quality of service is determined from the network connection
impairment factor and the performance impairment factor.
17. The device of claim 13, wherein
the quality of service is determined by adding together the network connection
15 impairment factor and the performance impairment factor.
18. The device of claim 13, further comprising:
means for determining an updated performance parameter from transmitting a
plurality of additional data packets; and
20 means for determining an updated quality of service of the connection from the
updated performance parameter.
19. A method comprising:
establishing a connection through a network for exchanging data packets that
25 represent voice between a first device and a second device;
determining a round trip time for data packets being exchanged through the
connection;
transmitting a plurality of the data packets along the connection;
determining at least one performance parameter from transmitting the data
30 packets; and

determining a quality of service of the connection from the round trip time and the performance parameter.

20. The method of claim 19, wherein:

5 the performance parameter is determined from a voice sample delay at a digital signal processing stage.

21. The method of claim 19, wherein:

10 the performance parameter is determined from a voice sample loss at a digital signal processing stage.

22. The method of claim 19, further comprising:

determining a network connection impairment factor from the round trip time; and

15 determining a performance impairment factor from the performance parameter, wherein the quality of service is determined from the network connection impairment factor and the performance impairment factor.

23. The method of claim 19, wherein:

20 the quality of service is determined by adding together the network connection impairment factor and the performance impairment factor.

24. The method of claim 19, further comprising:

transmitting additional data packets;

25 determining an updated performance parameter from transmitting the additional data packets; and

determining an updated quality of service of the connection from the updated performance parameter.

ABSTRACT

Devices, software and methods are provided for determining a quality of service
5 for a Voice over Internet Protocol (VoIP) connection. A round trip time of packets is measured between the devices that are exchanging voice data. In addition, at least one performance parameter is determined, such as packet delay or packet loss. A quality of service is then determined from the round trip time and the performance parameter.

10

DRAFT - 2010-09-10 - 10:56:50 PM

100




FIG. 1

200




FIG. 2

300




FIG. 3

PATENT APPLICATION
Attorney Docket No. 2705-133COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled, **DEVICES, SOFTWARE AND METHODS FOR DETERMINING A QUALITY OF SERVICE FOR A VoIP CONNECTION**, the specification of which:

- is attached hereto.
 was filed on _____ as Application No. _____
 and was amended on _____ (if applicable)
 with amendments through _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, Sec. 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Sec. 119 (a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)	Claiming Priority?		
<hr/> <hr/> (Number)	<hr/> <hr/> (Country)	<hr/> <hr/> (Day/Month/Year Filed)	<hr/> <hr/> <input type="checkbox"/> Yes <input type="checkbox"/> No

I hereby claim the benefit under Title 35, United States Code, Sec. 119(e) of any United States provisional application listed below:

<u>Provisional Application No.</u>	<u>Filing Date</u>
<hr/>	<hr/>

I hereby claim the benefit under Title 35, United States Code, Sec. 120 or §365(c) of any PCT international application designating the United States of America listed below,

insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Sec. 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Sec. 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application No.)	(Filing Date)	(Status) (patented, pending, abandoned)
-------------------	---------------	---

I hereby appoint the following attorneys to prosecute the application, to file a corresponding international application, to prosecute and transact all business in the Patent and Trademark Office connected therewith:

Customer No. 20575

<u>Attorney Name</u>	<u>Registration No.</u>
Jerome S. Marger	26,480
Alexander C. Johnson, Jr.	29,396
Alan T. McCollom	28,881
James G. Stewart	32,496
Glenn C. Brown	34,555
Stephen S. Ford	35,139
Julie L. Reed	35,349
Gregory T. Kavounas	37,862
Scott A. Schaffer	38,610
Joseph S. Makuch	39,286
James E. Harris	40,013
Graciela G. Cowger	42,444
Ariel Rogson	43,054
Craig R. Rogers	43,888

Direct all telephone calls to Gregory T. Kavounas at (503) 222-3613 and send all correspondence to:

MARGER JOHNSON & MCCOLLOM, P.C.
1030 S.W. Morrison Street
Portland, Oregon 97205

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole inventor: Thomas J. Hock

Inventor's signature:



10/23/00

(Date)

Residence: Chapel Hill, North Carolina

Citizenship: United States

Post Office address: 1015 Bugle Court
Chapel Hill, North Carolina 27516